PCT


WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : G08B 21/00	A1	(11) International Publication Number: WO 00/04521 (43) International Publication Date: 27 January 2000 (27.01.00)
(21) International Application Number: PCT/US (22) International Filing Date: 9 July 1999 (MX, NO, NZ, SG, VN, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT,
(30) Priority Data: 09/115,650 15 July 1998 (15.07.98)	τ	SE). Published With international search report.
(71)(72) Applicant and Inventor: O'BRIEN, Charles, T. 1451 Parkview Terrace S., Algonquin, IL 60102 (S);
(74) Agent: PERRONE, Mathew, R., P., Jr.; 210 South Management, IL 60102 (US).	ain Stre	et,
	÷	
·		

(54) Title: INTERACTIVE PRESCRIPTION COMPLIANCE AND LIFE SAFETY SYSTEM



(57) Abstract

An interactive prescription compliance and life safety system provides remote and on site verification of procedures related to the health status of a person, including taking of medicines (8, 9), responsiveness to queries (11, 12), and attendance of health care and service providers (18) in the home by providing for signals to and from a person's location (19, 20), with alarm activation (15) when a deviation from a preprogrammed procedure occurs.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
ΑT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moklova	TG	Togo
вв	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia ·	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of Americ
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
СН	Switzerland	KG	Kyrgyzstan	NO	Norway	zw	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
CM	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	Li	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

INTERACTIVE PRESCRIPTION COMPLIANCE AND LIFE SAFETY SYSTEM

This invention relates to correctly taking of Prescription Drugs through an interactive compliance system, which incorporates third party monitoring and interactive participation by the user of said drugs. Medical monitoring and personal safety and life safety are additional benefits to this invention.

Prior Art

10

15

20

25

30

35

While prescription drugs are modern miracles in preserving and extending a person's life, not taking prescriptions as required (non-compliance) has become a major health problem. Additionally people living alone, particularly the elderly, are subject to other incidents such as falls and drug reactions rendering them unable to call for help.

Non-compliance in prescription drug taking is putting an enormous strain on the entire health care system today. Estimates of cost to the United States economy range from 50 to as high as 100 billion dollars per year. It is estimated that 17 percent of all Emergency room visits are the direct result of a prescription drug misadventure (non-compliance). Other results of non-compliance include hospital and nursing home admissions as well as lost wages and lower productivity.

As the population ages, compliance becomes a source for even more concern. Population experts say by the year 2003, 83 million Americans will be over the age of 50, and by the year 2010, that figure will be over 100 million. Currently no system exists to compliance in the taking of prescription drugs. systems such as United States Patent 5,623,242 to Dawson/Byron April 22, 1997, provides that a signal is sent from a central data base containing all the pertinent information of the prescription individual pager reminding them to take the medication. However, such a system does not insure the medication has been taken. To ensure compliance, an interactive response should be sent back to the central database by the individual taking that specific medication. While drug compliance will go up using the pager system, patient response to the pager signal, or other alarm type signals, ensure an even higher compliance rate.

5

10

15

20

25

30

35

In-home safety and security is a growing concern for all people not just Americans. Safety and security companies have traditionally provided companies and wealthy individuals with services such as CCTV (closed circuit television), fire and burglar alarm monitoring and recently interactive video. Currently systems specifically for the home (wired or wireless) are now available. These services include smoke, fire, burglar, water, temperature, keyless door entry and carbon monoxide detection. Research in this area show specific patents but no central controller patent. United States Patent 5,673,016 to Lutes September 30, 1997, describes a visitor information system. While the communication links are available between the home or institution and safety/security companies, "an Interactive Prescription Compliance System" is not offered. Wireless systems for compliance safety and security simply are not in the United States Patent database. United States Patent 5,625,338 to Pildner April 29, 1997, wireless keypad to control communications to a control panel for entrance and exit control. United States Patent 5,598,427 to Arthur, January 28, 1997, appears to be a burglar alarm system.

Continuing with in-home systems; pill or medication dispensers form home use such as United States Patent 5,405,011 to Haber April 11, 1995, United States Patent 5,575,392 to Cutler November 1996, and United States Patent 5,641,091 to Danes/Havar June 24, 1997, do not incorporate the latest technologies such as bar codes or RFID tags, but rather are mechanical in nature. United States Patent 5,609,268 to Shaw March 11, 1997, is a microprocessor controlled pill dispenser, but it too

10

15

20

25

30

35

fails to incorporate interactivity with the user and does not use other interactive components such as bar code and RFID technology. Drug compliance can now be assured with such dispensers.

Bar codes and RFID tags are by their very nature wireless interactive or active devices. readers and RFID tag readers by design could be wired to a fixed point or wireless. U. S. Patent 5,640,002 Ruppert June 17, 1997 is a portable (wireless) RFID tag and bar code reader for grocery stores. United States Patent 5,646,592 to Tuttle July 8, 1997, is a RFID tag for security of containers such as suitcases. States Patent, 5,602,380 to Bishop February 11, 1997, is a line of sight bar code scanner/reader using infrared technology. United States Patent 5,721,421 to Van Doukeluur February 24, 1998, is a wireless bar code reader used for identifying shelf tags. The required information is then transmitted to a terminal processed and then retransmitted to an RF to a base station. All these systems have the following features in common: merely state of the art technology, (2) consumer product and interactive prescription compliance Therefor, drug compliance is not an obvious benefit of these systems.

U.s. Patent 5,700,998 to Palti December 23, 1997, uses bar code technology. A bar code is printed on pills and a bar code assigned to a patient. If the patient's bar code does not match the pill bar code, an alarm is generated indicating a mismatch of patient and medication. This system appears to be institutional in nature, as does United States Patent, 5,713,487 to Coughlin February 3, 1998, an automated medication system using bar codes and manipulating arms. U. S. Patent 5,564,803 to McDonald October 10, 1996, is a portable nursing center utilizing bar codes and a keyboard data entry system to open specific drawers containing medications. While these systems seem to ensure some form of compliance, none provide for

personal safety and security.

5

10

15

20

25

30

35

Cable Set Top Boxes are becoming commonplace in homes, assisted living centers, retirement centers, nursing homes, hotels and adult day care centers. United States Patent 5,512,935 to Majeti April 30, 1996, appears to be a cable set top box which flashes messages to individuals on personal computers. United States Patent, 5,649,283 to Goller July 15, 1997, is a device used to ensure the correct programming is being received at the television set of a consumer. United States Patent, 5,631,903 to Dianda May 20, 1997, is a cable set top box which controls television sets. U. S. Patent 5,727,052 to Sizer March 10, 1998, is a system to record and display information at a remote location using that location's recording unit over a telephone network. Cable set top boxes today do not have the capabilities of receiving wireless data from sensors placed in the home or institutional settings. They also do not have bar code or RFID readers or telephone jacks to reach a customer service center via the PSTN or the cellular network. Until now there has not been a need for such features.

If a means were developed to remind patients to take medication correctly or at prescribed intervals whether at home or away, plus add the feature of assuring compliance through interactive emergency room visits, hospital or nursing admissions would be greatly reduced. Couple the drug compliance feature with medical monitoring such as, but not limited to, electrocardiogram, oxygen and renal, plus in home or room safety and security. Medicaid, third party insurance and personal financial costs would be reduced dramatically. An additional Benefit would be the monitoring time spent by visiting nurses through electronic time cards. The visiting nurse enters in a PIN code identification number upon arrival and repeats the procedure upon departure, thus verifying and recording time spent with a patient,

10

15

20

25

30

35

eliminating a major source of Medicare fraud. Other service providers, such as therapists, oxygen delivery person or Meals-On_Wheels people, could also be assigned a PIN code identification number. All of the data would be stored int he Customer Service Center and available to the care givers, government programs (Medicare/Medicaid) doctors and insurance companies for each patient.

PCT/US99/15612

My Interactive Prescription Compliance System uses a PSTN, bar code readers, wireless monitoring devices and a cable set top box like console. By PSTN is meant phone system telephone network. Provisions in the console have incorporated, through interconnections and stuffing options, to add automated prescription dispensers, cellular phone lines, cable and broadcast Tv inputs and pager or palm pilot-like devices.

Functionality of all of these features described have been developed in theory and through custom Interactive Prescription work in my electronics Presently the research of existing Compliance System. systems reveals no clear complete and total embodiment of the proposed patent I have submitted. The cost for the care of terminally ill patients such as AIDS and cancer patients, plus the growing aged population, would become substantially less with the use of my Interactive Prescription Compliance System. Use of this system would reduce the chance of non-compliance by over medication.

ADVANTAGES OF INTERACTIVE PRESCRIPTION COMPLIANCE SYSTEM PATENT

- A. Prescription drug compliance increased
- B. Utilizes new technology combined with existing devices
 - 1. ASIC Semiconductors (application specific integrated circuit)
 - 2. Bar code scanners and readers
 - 3. RFID tag scanners and readers
 - 4. Bar code labeled or RFID tagged

	prescription vials or microprocessor
	controlled prescription dispensers labeled or
	tagged with same
	5. Use of 433MHZ and 900MHZ band for home
5	sensor and cordless phone
	6. Use of 125KHZ, 13.%^MHZ and 2.45GHZ band
	for RFID tags.
	C. Interactive response required by patient to
	central station
10	1. No response to reminder patient is
	called
	Still no response caregiver is dispatched
	to site
	D. Personal safety and security
15	1.Fire, burglary, water, temperature,
	electricity, carbon monoxide alarms, panic
	buttons (Help Me I've Fallen Down), perimeter
•	monitoring (Alzheimer patient) keyless entry
	systems, interactive video/audio
20	E. Visiting nurse and other caregiver monitoring
	(Meals-On-Wheels, therapists, etc.)
	F. Medical monitoring electrocardiogram, renal,
	oxygen, etc.
	G. Individual patient monitoring through
25	Interactive Video
	H. Central Station monitoring and database
	storage of compliance on noncompliance
	 Reports of all activities available to all
	interested parties
30	INTERACTIVE PRESCRIPTION COMPLIANCE
	AND LIFE SAFETY SYSTEM DRAWINGS
	Figure 1: Rendering of Interactive Prescription
	Compliance System Drug Dispenser;
	Figure 2, Figure 5 and Figure 6:
35	Flowchart of Interactive Prescription Compliance
	System Box showing Prescription Dispenser utilizing
	bar code or RFID tag technology also shown optional
	Palm Dilot or Reener-like device ontional wideo

camera, optional cellular phone, wireless life safety devices and wireless panic buttons;

- Figure 3: Home Interactive Prescription Compliance
 System Architecture with Compliance Set Top
 Box and Interactive Audio Visual option;
- Figure 4: Institutional Interactive Prescription
 Compliance System Architecture with Compliance
 Set Top Box and Interactive Audio Visual
 option;
- Figure 7: Prescription vial, being either bar coded or RFID tagged.

5

15

20

25

30

35

<u>Description of Figure 1</u> -- Interactive Prescription Compliance System Drug Dispenser.

Referring to Figure 1, major components consist of housing 110 which conforms to all applicable standards for UL 2034 specifications. Bar code or RFID tag 1.11 affixed to housing by means of printed bar code label or Information contained in bar preprogrammed RFID tag. code or RFID tag 1.11 will be used to activate some, but not all command controls in the Customer Service Center (Figure 3 and Figure 4 to Interactive Prescription Compliance System Set Top Box Figure 2.) electronics 1.12 are microprocessor based utilizing standard cell and ASIC designs and receiver input from compliance set to box (Figure 2) by means of a communications link present via a connector which is Interactive Prescription Compliance of the part Dispenser Stand 1.15 which affixed to Interactive Prescription Compliance Set Top Box Figure 2. electronics microprocessor based 1.12 processes data received from Customer Service Center, Figure 3 and Figure 4, and activates miniature stepper motor and A prepackaged single dose serrated spindle 1.13. medication packet spooled containing at least a one week supply of meds 1.14 is then dispensed at correct intervals, one packet at a time from data supplied from custom electronics 1.12 and rotated out of dispenser by multiple motor spindle 1.13. the case of In

10

15

20

25

30

35

prescription drugs prepackaged spool of meds 1.14 will packaged according to prescription directions provided by patients doctor and filled at mail order facility, Figure 3 and 4. Each individual prepackaged medication packet shall be of cellophane-like material and have printed on it patient name, drug name, doctor's name, other information could be added as required. An extension cord-like cable of sufficient length could be affixed to the dispenser allowing a bedside or chair side use of said dispenser. It is possible to completely control this dispenser by the Customer Service Center. This is accomplished by control signals sent by the Customer Service Center dispensing packets or "locking" the dispenser. The dispenser is CPU based with flash memory, which allows complete control.

<u>Description of Figure 2</u> -- Interactive Prescription Compliance Console.

Referring to Figure 2, the completely Interactive Prescription Compliance Console is a microprocessor based system which utilizes cable set top box technology plus unique features relating to compliance and safety for the individual user.

Figure 2 illustrates in block diagram form the theory of operation beginning with normal broadcast cable television signals (2.1) received by the users' Compliance Console and in the case of a cable signal are then processed by the channel 3 demodulator 2.2 or in the case of a broadcast signal, Section 2.2 is designed with circuitry to directly pass signal to the user's television set. Continuing with Figure 2, the cable signal is demodulated then digitized and synchronized (2.3) and passed to the channel 3 modulator (2.5). cable signal is then modulated (2.5) and sent to user's television. Channel selection is accomplished by use of standard wireless infrared emitter/detection circuit (remote or clicker). The cable broadcast signal could be completely independent of the systems CPU (2.7) and the video overlay circuit (2.4).

More particularly, an appropriate group of parts for carrying out the functions of this invention are as follows:

	SET TOP BOX STAN	DARD FEATURES
5	1. CPU	
•	•	state memory
	•	dio frequency) Receiver
		including RS232, RJ11, RJ45, PCMCIA,
	_	mart card
LO	5. user i	nterface with alarm and reset buttons,
	for ex	ample PS/2 Type Key board
	6. Displa	y (liquid crystal or other readout)
	7. Video	Overlay Circuit
	8. Audio	or Visual Alarm
15	9. Bar Co	de or Radio Frequency Identification Tag
	(RFID)	Reader or Scanner
	10. Drug D	Dispenser Port
	11. Modem	(preferably 56 K or better)
	12. Etherr	et 10 Base T Converter or WAN equivalent
20	13. Auto I	Dialer
	14. Stand-	by Battery Power 24 Hr. Min.
	15. Priori	ty Interrupt
	SET TOP BOX OPTI	ONAL FEATURES
	1. Wirele	ess Safety and Security Devices
25	a. I	rire Alarm
	b. E	Burglar Alarm or Motion Detector
	c. T	Cemperature Sensor
	d. (Carbon Monoxide Detector
	e. V	Nater Sensor
30	f. I	Electricity Sensor
	g. I	Panic Buttons, for example wireless
	F	personal safety wrist or pendant button
	h. I	Perimeter Limiting Alarm (Alzheimer
	I	Patient Wandering Off)
35	i. V	Jideo Camera
	j. j	Keyless Door Entry
	2. Displa	ay Pager

Cellular Telephone or wireless telephone

З.

4. Drug Dispenser

5

10

15

20

25

30

35

5. Interactive Audio or Video medical monitors, including but not limited to, electro cardiogram, renal function, oxygen and blood pressure.

The System (Figure 2) will contain DRAM and FLASH Memory (2.13) sufficient enough to allow for the operation of all options: RF Receiver/wireless monitors (2.6), Display Pager (2.11), Cellular Phone w/Display (2.12), Interactive Video (2.16) and Panic Button (2.17). The Flash Memory section of the system (2.13) also allows the Customer Service Center (Figure 3, Section 314 and Figure 4, Section 414) to communicate new prescription information and also to allow control by the Service Center to turn on/turn off or reprogram other features of the system, including the ability to lock the Prescription Dispenser System (Figure 1).

The Interactive Prescription Compliance Console has been designed with multiple unique features to assure maximum prescription drug compliance and safety. CPU 2.7 has been programmed with a unique address (PIN code) also configured to accept packetized data through circuity designed in section 2.20 which interfaces with the PSTN or a 10 BASE T system. The 10 BASE T system is part of the Ethernet system. A bar code/RFID tag reader (2.8) has been incorporated with the interactive system. It is required to correctly identify the user and the user's bar code or RFID tag of the prescription vial, Figure 7, and/or also to identify the user and the users bar code or RFID Tag of Drug dispenser (2.9). Dispenser is connected to the Interactive Prescription Compliance System through a cable and RS232 port like connection which is present on both the Set Top Box (Figure 2) and Drug Dispenser and stand (Figure 1).

Interactive Compliance could be accomplished by user removing serrated package of medication breaking the infrared emitter detector circuit dispenser 1.16. The meds are automatically dispensed per SIG (dosage and

intervals) recommended by the doctor and programmed in the Customer Service Center. That circuit interruption generated a signal to dispenser custom electronics (1.12) to Interactive Compliance Reminder System Set Top Box CPU 2.7 (Figure 2) to Customer Service Center, which stores in its database that the meds package has been removed and compliance has occurred.

5

10

15

20

25

30

35

Another Interactive Compliance method would be to pass the pill vial (Figure 7) in front of the bar code/RFID tag reader after alarm reminder signal has been set by Customer Service Center to users, Interactive Prescription Compliance Console reminding user to take medication. Such action taken by user (bar code/RFID Swipe) generates a signal to CPU (2.7) back to Customer Service Center identifying which prescription medication user is about to ingest. If the bar code RFID tag information on Medication Pill Vial (Figure 7) does not match medication information at Customer is immediately notified by Service Center, user If information supplied telephone or other means. matcheD, Customer Service Center records the Compliance event in its database. An extension core like cable could be affixed to reader allowing for bedside or chair side use.

If the user does not respond to the alarm reminder signal after two (2) attempts by the Customer Service Center, the primary caregiver would be notified. This action would ensure the user would be in compliance. Dates, times of non-compliance, as well as caregiver notification are recorded in the Customer Service Center data base.

The keyboard of the System (2.18)will be cable set top box PS2 type conventional with alarm buttons having accessorized interrupt on the users telephone line and direct dial capabilities to the fire and police departments (911), Customer Service Center and to the designated caregiver. An optional compliance button could also be added which

10

15

20

25

30

35

would be depressed by the user. It would be depressed only after the user had swiped the prescription vial past the bar code (RFID) tag reader and matched the data present in the Customer Service Center. Pressing the compliance button would generate a signal back to the Customer Service Center that complete compliance had These buttons will be marked in accordance symbols complying with Americans the with Disabilities Act. Additional auxiliary buttons, will be able to be programmed by the user to call other entities on a priority basis such as a doctor or next-door The keyboard will be physically enlarged and back light to allow for easier use by the sight impaired or the physically handicapped. The keyboard (2.18) would also be the means of having visiting nurse, therapist, caregiver, meals on wheels or medical equipment provider record when these services and goods An identification number (PIN code) were provided. would be assigned to these individuals. Log-in and logout entries would be required of these service providers to alert the Customer Service Center of the Dates and Times service and goods were provided to user. Failure to log-in or log-out by these individuals would result in an alarm condition at the Customer Service Center and notification of same would be conveyed to the users' primary caregiver.

The color liquid crystal display (2.14) will be of sufficient size and back light allowing the user of average or slightly has than average eye sight to see the Interactive Compliance Reminder Message. "Mrs. Jones 3 PM Tuesday, March 17 take your blood pressure medication." Other information could be displayed showing the user the size shape and color of the medication to be taken or special instructions like -- "take with meal" "take with mild". this display could also be an unlit black and white LCD.

Audio visual alarms (2.15) are also a permanent feature of the Interactive Prescription compliance

As the drug compliance message is generated System. from the Customer Service Center and transmitted to the users Set Top Box LCD Displays and additional subcarrier signal activating the audio/visual alarm. consists of a piezoelectric like speaker with an audio output level of approximately 85DB and a flashing LED. the audio alarm and flashing LED will alert user that a predetermined time has elapsed and the user is required to take more medication. This alarm unit will continue intermittently beeping and flashing for a period of three minutes or until the compliance button has been pressed. Failure to press the compliance button within three minutes results in a system reset and the Compliance signal is retransmitted from the Customer Service Center and the three minute alarm is again sent Failure for a second time to respond by to the user. the user within three minutes, generates an alarm condition at the Customer Service Center. A telephone call is then placed by the Customer Service Center to Failure by the user to respond results in the user. the Customer Service Center contacting the authorities to check condition of user. This audio/visual alarm could be wired with an extension cord-like cable of sufficient length to allow it to be placed next to a bed, chair or central location. This alarm could also be wireless.

10

15

20

25

30

35

The Video Overlay Section (2.4) of the Interactive Prescription Compliance System allows compliance reminder special instructions and even advertising to be scrolled across the bottom of the users television set. This messaging would not disturb the current programming but would rather be like a weather service "Severe Thunderstorm Warning" generated by the Customer Service Center. "Mrs. Jones, it is time to take your blood pressure medication, please remove your medication from the dispenser." Or without a dispenser -- "Mrs. Jones, it is time to take your blood pressure medication, please pass the prescription vial in front of the bar

code/RFID Tag Reader."

5

10

15

20

25

30

35

The system will also be equipped with an RF Receiver, usually either 433MHZ or 900MHZ (2.6). This receiver will allow the user to add wireless sensors carbon monoxide, temperature, smoke, such as electricity, burglar alarm, keyless door entry, wireless perimeter alarm (a device to notify Customer Service Center or caregiver that the user has gone beyond prescribed boundaries) and panic buttons (Help I've Fallen Down) (2.17). connection to the Customer Service Center of these sensors will be accomplished through an automatic dialer activated by the sensors or panic button generating a priority dial and alarm signal. All of these alarms sensors are currently available on the open market and the RFID receiver has been designed with custom ASIC devices to accept the sensors output. Other wireless sensors will be added but not limited to oxygen, electrocardiogram, renal and blood pressure.

Input of data to the Interactive Prescription Compliance System will be accomplished through use of RS232 type ports, RJ11 style telephone connectors and PCMCIA slots (2.10). Other input devices are an Ethernet adapter or 56k Modem (2.19). These built in interconnects allow the System to communicate to the Customer Service Center or other sites through the PSTN, Cable, Ethernet (Lan & Wans) or the optional cellular phone connection (2.12).

An interactive audio/Video camera system connection (2.16) may optionally be installed on the Interactive Prescription Compliance System Set Top Box. This connection will be accomplished through custom logic and an RS232 type multifunction cable/connector, thus allowing the Customer Service Center and other individuals to view the user via the PSTN or Internet. Other viewing options can be accommodated such as a hard wired system.

Referring to Figure 7, the Display Pager-like device allows the user freedom to move away from the

10

15

20

25

30

35

user's home or room. The user or Caregiver notifies the Customer Service Center of plans to by Physically away from the Interactive Prescription Compliance System for an extended period of time. This notification can be accomplish via the conventional PSTN or optimal cell If the user has a system using a dispenser, Figure 1, the Customer Service Center then transmits the data stored in the Center for the user causing the to dispense the medication dispenser, Figure 1, necessary for the period of time user will be away from The pager-like device would be on the primary system. line with the Customer Service Center the Interactive Prescription Compliance System. System and pager-like device would have the same The pager-like device would be telephone number. equipped with reprogrammable memory and battery This feature allows the Customer Service operated. Center, with prior user notification, to download the SIG) dosage and interval information) and alarm data and time to this pager-like device. This would allow the user to take the device and medication away from the The user would be notified by audio home or room. beeper-like signal or vibration and a text message displayed on the pager. Downloading of data and battery charging of the pager to the Interactive Prescription Compliance System would be accomplished by a standard connection, such as an RS232 port connecting the pager stand and the System. The pager stand would contain a battery charger, which would be connected by a line cord to a conventional AC consumer outlet.

Referring to Figure 6, the cellular telephone has a dual function. The cellular telephone could be primary voice and data links to the Interactive Prescription Compliance System. This would thereby eliminate the hare wired connection to the Customer Service Center and the PSTN. An additional function is off premise notification to the user of the SIG (dosage intervals). compliance of prescription drug taking

would occur by contacting the Customer Service Center to dispense the correct amount of packetized medication from the Interactive Prescription Compliance Drug dispenser (Figure 1). The user would then physically take the medications dispensed and the Customer Service Center would simply call the user's cellular phone and advise same which medication to take at the correct time.

5

10

15

20

25

30

35

Economics of scale require the Interactive Prescription Compliance System to be manufactured using multilayered and socketed Mother/Daughter Board techniques, using this procedure allows levels of service for the options available to the basic system. The basic system specifications and staffing for level of service options are defined.

HOME INTERACTIVE PRESCRIPTION COMPLIANCE AND LIFE SAFETY SYSTEM

Referring to Figure 3 and Figure 4, the patient's doctor writes prescription containing the following information: patient's name, doctor's name, drug name indicating whether or not generic replacement is acceptable, drug strength, drug quantity, SIG (dosage intervals) and amount paid. The pharmacist requires the following in addition to information provided on prescription form: patient's address, patient telephone number, date of birth and sex. The pharmacist creates the following information: Rx number, refill number, date and time sold. All of this information is entered into the pharmacy data entry workstation. workstation is networked to the bar code label printer using an RS232 port and creates the label and unique bar code for the patient. The entire patient prescription data packet is sent to the pharmacy data processing 3.3 and 4.3 and is compared prescriptions the patient may also be taking or has on If there are other prescriptions present in the data processing center, data base 3.3 and 4.3, for the same patient, drug interactions are possible because

10

15

20

25

30

35

some patients have multiple doctors. If a drug interaction is found, the data processing center 3.3 and 4.3 then the established communication link satellite, PSTN, Lan or WAN, notifies filling pharmacist. This is an added precaution. If there are no drug interactions, the pharmacy system creates prescription label including a patient specific bar code. The new technology of RFID tags are created using the same procedure. Obviously the label is created by the read/write RFID tag is programmed by the RFID tag programmer present in the prescription filling pharmacy, 3.1, 3.2, 4.1 and 4.2. the prescription is then filled the label/bar code or label RFID tag are affixed to the vial, Figure 7. bar code or RFID tag will contain, but not be limited to, the patient's name and unique prescription number. Other patient information will be stored in the filling pharmacy data base.

The mail order pharmacy, 3.2 and 4.2, fills prescriptions ailing the identical procedures of the retail pharmacy. Two additional functions are performed at this site. First the filling of the dispense with packetized medication is completed, including application of pharmacy bar coded label on RFID tag. Second, the mail order facility does exactly as prescribed; delivers the pill vial or interactive drug dispense to the patient's extended care address or home.

Nightly procedures for both the retail pharmacy and the mail order pharmacy is to download the prescription data from the pharmacy data entry work station to the store or mail order pharmacy server (3.1, 4.1, 3.2, 4.3). this data is then data compressed, packetized and transmitted to the data processing center (3.3 and 4.3) frame relay, PSTN, POTS, LAN, WAN, and Satellite transmission lines could be used. The download to the data processing center occurs at off peak hours usually 2 am Central Standard time.

Continuing with Figure 3 and Figure 4, the data processing center is the central location of all

patient, doctor, prescription, insurance, bar code or RFID tag data. This allows the modern pharmacy chain store and mail order facilities to secure nationwide and soon worldwide central data storage, thus service as the pharmacy drug information source for the Customer Service Center (3.4 and 4.4). the interactive communication link between the data processing center (3.3 and 4.3) and the Customer Service Center should be a dedicated T2 type or better, or satellite connection. The data processing center (3.3 and 4.3) download all patient doctor prescription insurance, bar code or RFID tag information to the Customer Service Center (3.4 and 4.4 on a daily basis. The following is then received

- 1. Patient's name, address, phone number, sex, data of birth
 - 2. Doctor's name, address, phone number, other doctors' prescriptions
 - 3. Prescription number

from the data processing center:

- 4. Bar code/RFID tag code
 - 5. Number of refills
 - 6. Drug type (generic ok)
 - 7. Quantity

5

10

20

30

- 8. Date and time sold
- 9. Interactive Compliance Reminder Set Top Box
 - 10. Pager serial number
 - 11. Accessory list
 - a. Wireless alarms
 - b. Interactive audio visual
 - c. Cellular phone number
 - d. Pager serial number
 - e. Interactive Compliance Reminder
 Prescription Dispenser serial number
 (Figure 1)
 - f. Billing method (credit card, check or cash)
 - g. Insurance company information
 - h. Medicare/Medicaid

Continuing with Figure 3 and Figure 4, the Customer Center receives the patient pharmacist information and stores the data. The Customer Service Center contacts the user via PSTN lines or other communications following links, and obtains the information:

- 1. Patient's name, age, sex, prescription number
- 2. Doctor's name, address, telephone number
- 3. SIG, dosage amount and time of day
- 10 4. Number of refills

5

15

25

- 5. Drug type
- 6. Quantity
- 7. Date and time prescription bought or received
- 8. Interactive Prescription Compliance Set Top
 Box serial number
- 9. Primary care giver name, address and phone number
- 10. Call list of other care givers
- 11. Accessory list
- 20 a. Wireless alarms
 - b. Interactive audio visual
 - c. Cellular phone number
 - d. Pager serial number
 - e. Interactive Prescription Compliance
 Dispenser serial number
 - f. Billing method (credit card, check or cash)
 - g. Insurance company
 - h. Medicare/Medicaid

After Customer Service Center conducts live interview with patient or caregiver, the data collected is entered in the main frame data bank and compared to the pharmacy data for errors. If none are found, the Initialization Procedure for the Interaction System begins.

INITIALIZATION:

- 1. Determine user phone tone or pulse (dial 9)
- 2. PIN number assigned System Set Top box

WO 00/04521 20

Drug Dispenser 3. PIN number assigned to (optional)

Level of service 4.

5

10

15

20

25

30

35

Turn on wireless alarms, Interactive a. Pager, other monitoring Audio/Video rental, devices (oxygen, electrocardiogram)

PIN number other service provides 5.

Visiting nurse, meals on wheels, medical a. equipment suppliers. (This feature is effective in eliminating extremely Medicare/Medicaid fraud by requiring other service providers to log-in and log-out to identify service or goods provided. This is accomplished through the keyboard or bar code/RFID tag reader on the Interactive Compliance Reminder Set Top Box.)

System test 6.

The Customer Service Center will license from First Data or other sources, Medispan pharmacological information such pill size, shape, color, drug interaction/reaction and special ingestion instructions. This information will be sent to the user and displayed concurrently with the Compliance Alarm This information is identical to Message Signal. pharmacy providing the contained in information prescription.

Description of Figures 3 and 4 -- Home Interactive Prescription compliance System Architecture Compliance Console and Interactive Audio Visual Option Institutional Interactive Prescription Compliance System Architecture with Compliance Set Top Box and Interactive Audio Visual option.

Referring to Figure 3 and 4, after initialization is completed, the Interactive Prescription Compliance Set Top Box functions in an identical manner, whether in the users' home, assisted living center or retirement

community. The initialized version of Figure 4 may use a LAN or WAN.

More particularly, a flowchart of personal information required and data storage location can be set out in chart form. A suggested chart form is as follows:

5

Data Processing Center Customer Service Center Doctor Name, address, phone number Data Processing Center data Patient Name, address, phone number received Telephone interview w/patient to . Drug Name/quantity (generic) 10 recheck data processing center info, . SIG dosage & intervals date/time prescription received, . Number of refills installation of system, Set Top Box . Prescription number pin number, number of primary . Date and time sold 15 caregiver, name, address, phone . Dispenser bar code/RFID tag . Bar code or RFID tag code Emergency phone numbers . Drug interaction/reaction check service providers pin numbers, police, fire, hospital, etc. . Serial number Set Top Box . Options, wireless alarm, medical Initialized Set Top Box and monitors, pager number, wireless 20 options phone number System check Software updates . Supplier advertising Pharmacological data Options added/deleted 25 Medispan/First Data New drug regimens .Billing method (credit card, Source of all exception reports lease check, cash, Medicare, Medicaid) Compliance - Insurance - Alarm -30 and Service Providers Level service letter sent to patient - caregiver Pharmacy Retail or Mail Patient Room, Apt. or House Order . Doctor name, address, phone number System installed Telephone interview with customer . Patient name, address, phone

System installed . Doctor name, address, phone number
Telephone interview with customer . Patient name, address, phone
number
service center - level of service date of birth, sex
checked . Drug name, quantity, generic,

SIG

check, bar code swipe--RFID swipe . Date, time sold
Interactive Compliance Reminder . Bar Code or RFID Tag code

System fully functional

. Drug interaction/reaction check

Mail order (load medicines in optional dispenser or fill bar coded or RFID tag prescriptions)

Options, wireless alarms, medical monitors, pager number, cell

phone number

Billing method (credit card,

10 lease,

5

15

20

25

30

35

40

check, cash, Medicare/Medicaid. --

Referring to Figure 5, this is a block diagram of information collected by the pharmacy processing center and Customer Service Center. Figure 5 also shows where the collected data resides in each facility. This graphically depicts how interactive and redundant the system is, thus assuring correct Options such as wireless alarm, service medication. provider PIN numbers also redundantly checked, depicted here in Figure 5. Any changes in drug regimen are downloaded from the Customer Service Center to the user's Interactive Prescription Compliance System. These changes are accomplished utilizing the PSTN and the user's system reprogramable memory, preferably with redundant data at the customer's site.

<u>Description of Figure 7</u> -- Prescription vial bar coded or RFID tagged.

Referring to Figure 7, the pill vial for prescription drugs is available in numerous sizes. This figure is intended to depict where the RFID tag might be affixed to the vial. In most instances the prescription or RX label is affixed to the vial body and contains the barcode if used in lieu of RFID tag. This figure as stated depicts a prescription drug vial. However, the RFID tag and prescription (RX) label with barcode could also be affixed to liquid containing bottles and squeezable toothpaste-like tubes.

Statistics for costs of long term care and age projections in Illinois are similar to the national figures. Those statistics may be summarized as follows.

Illinois Long-Term Care Facts
1997 United States Census Bureau Statistics
Long-Term care facts:

Almost half of Illinoisans aged 65 or older will eventually need long-term care. Such care could include in-home help with the activities of daily living, such as dressing or bathing, or it could include skilled medical attention given in a nursing home.

Illinois' average cost of one year of long-term care is \$13,000 for in-home services and \$36,500 for a nursing home, with inflation adding another 6% per year.

Projected Distribution of the Elderly Population by Age

Percent of Elderly Population

15 Age Group 1985 2010 2035 2050

5

10

25

30

35

65 to 69 32.2 29.9 24.0 24.6

70 to 74 26.6 21.8 24.3 20.0

75 to 79 19.6 17.4 21.0 17.1

80 to 84 12.2 14.0 14.8 14.6

20 85 to Over 09.4 16.9 16.0 23.7

A large multi-employer pension fund recently reported that their retirees for the first time ever, out number the active participants. This trend will continue to be seen in other pension funds in the future.

Using state of Illinois facts, United States Census Bureau statistics and recent newspaper articles, the need for an Interactive Prescription Compliance and Life Safety Monitoring System is dramatically illustrated. The aging of Americans is accelerating at an alarming rate. Also accelerating at alarming rates are Medicare and Medicaid fraud and elderly care costs. These articles and statistics support the need for my patent application.

This application -- taken as a whole with the specification, claims, abstract, and drawings -- provides sufficient information for a person having ordinary skill in the art to practice the invention disclosed and claimed herein. Any measures necessary to

practice this invention are well within the skill of a person having ordinary skill in this art after that person has made a careful study of this disclosure.

Because of this disclosure and solely because of this disclosure, modification of this method and apparatus can become clear to a person having ordinary skill in this particular art. Such modifications are clearly covered by this disclosure.

What is claimed and sought to be protected by

Letters Patent is:

25 CLAIMS

- 1. An interactive personal safety system for a person comprising:
- (a) an outward communication means being connected to a customer service center;
- (b) a personal activating means connected to the outward communication means;

5

10

15

20

25

- (c) an automatic activating means connected to the outward communication means;
- (d) a programmable timing mechanism interconnecting the outward communication means, the personal activating means, the automatic activating means and the customer service center;
- (e) the programmable timing mechanism being adapted to connect the automatic activating means to customer service center, when the personal activating means fails to activate for at least one preset time;
- (f) a return communicating means connecting the customer service center to the outward communication means:
- (g) a response means being connected to the customer service center; and
- (h) the response means activating a team indicator so that the return communication means can require an appropriate assistance team upon failure to respond to a notice from the return communication means.
- 2. The interactive personal safety system of Claim 1 further comprising:
- (a) the personal activating means being at one least one selected from the group consisting of a telephone, a home sensing device, at least one bar code, and at least one radio frequency identification tag; and
- (b) the response means being connected to the team and the return communication means through the customer service center.

3. The interactive personal safety system of Claim 2 further comprising:

(a) the at least one bar code and the at least one radio frequency identification tag providing at least one identification mechanism;

5

10

5

5

10

- (b) the at least one identification mechanism being a applied to a functional member selected from the group consisting of at least one caregiver and at least one medicine; and
- (c) the programmable timing mechanism being activatable by the at least one identification mechanism.
- 4. The interactive personal safety system of Claim 3 further comprising:
- (a) the programmable timing mechanism requiring activation for at least one predetermined time by the at least one identification mechanism; and
- (b) the automatic activating means being triggered upon failure to meet the at least one predetermined time.
- 5. The interactive personal safety system of Claim 4 further comprising:
- (a) the programmable timing mechanism including at least one set off alarm mechanism selected form the group consisting of a fire alarm, a burglar alarm, a water alarm, a temperature alarm, an electricity alarm, a carbon monoxide alarm, a panic button alarm, a perimeter monitoring alarm, a keyless entry systems, an interactive video alarm, and an interactive audio alarm;
- (b) the programmable timing mechanism including at one human code selected from the group consisting of a nurse code, a meal server code, and a therapist code; and
 - (c) the programmable timing mechanism including at one medical code selected from the group consisting of an electrocardiogram, a renal monitor, and an oxygen monitor.

27

6. The interactive personal safety system of Claim 5 further comprising:

- (a) the interactive video providing monitoring for an individual patient;
- (b) the interactive audio providing monitoring for an individual patient;
- (c) the customer service center including a database storage of information relating to compliance based on data from the personal activating means and the automatic activating means; and
- (d) a recovery means for recovering data from the data base storage.
- 7. The interactive personal safety system of Claim 6 further comprising:
- (a) the outward communication means including a set top box;
- (b) the set top box having a communication link with the customer service center;
- (c) the set top box including an electronics microprocessor to processes data received from the customer service center; and
- (d) a medicine supply being activatable through the set top in order to dispense at least one medicine from the medicine supply at least one desired interval.

5

10

5

PCT/US99/15612

5

10

15

5

- 8. The interactive personal safety system of Claim 7 further comprising:
- (a) the return communication means including a television activating means cooperating with the set top box; and
- (b) the set top box including at least one feature selected from the group consisting of a computer processing unit, a solid state memory support, a radio frequency receiver, at least one connecting port, a user interface having at least one alarm button and at least one reset button, a display device, a video overlay circuit, an audio alarm; a visual alarm, bar code, a radio frequency identification tag reader, a radio frequency identification tag scanner, a drug dispenser port, a modem, an ethernet 10 base t converter, a wide area network converter, an auto dialer, a back-up power source, and a priority interrupting system.
- 9. The interactive personal safety system of Claim 8 further comprising:
- (a) the set top box including at least one item selected form the group consisting of a wireless safety device, a security device, a display pager, a cellular telephone, and a wireless telephone; and
- (b) the set top box being connected to at least function selected from the group consisting of a drug dispenser, an interactive audio medical monitor, and an interactive video medical monitor.

PCT/US99/15612

WO 00/04521 29

5

10

5

5

10

- 10. The interactive personal safety system of Claim 9 further comprising:
- (a) the interactive audio medical monitor and the interactive video medical monitor being at least selected from the group consisting of an electro cardiogram, a renal function monitor, an oxygen monitor and a blood pressure monitor; and
- (b) the wireless safety device and the security device being at least selected from the consisting of a fire alarm, a burglar alarm, a motion detector, a temperature sensor, a carbon monoxide detector, a water sensor, an electricity sensor, a wrist mounted panic button, a pendant panic button, a perimeter limiting alarm, a video camera and a keyless door entry.
- 11. The interactive personal safety system of Claim 10 further comprising:
- (a) the bar code serving to correctly identify a user or a medicine; and
- (b) the radio frequency identification tag serving to identify the user and the medicine.
- 12. The interactive personal safety system of Claim 11 further comprising:
- (a) the bar code and the radio frequency identification tag providing log-in and log-out entries for at least one service provider and alerting the customer service center of the dates and times service and goods were provided to user; and
- (b) a failure to log-in or log-out causing an alarm condition at the customer service center and follow-up notification.
- 13. The interactive personal safety system of Claim 12 further comprising:
- (a) the alarm condition including a delay in order avoid unnecessary action; and
- (b) the alarm condition including at least one audio warning.

5

10

15

20

- 14. The interactive personal safety system of Claim 13 further comprising:
 - (a) a billing function being connected therewith;
- (b) a personal identification number being placed in the set top box;
- (c) an adjustable service level being provided to the set top box; and
- (d) a testing mechanism for the interactive personal safety system.
- 15. An interactive prescription compliance and personal safety system, requiring both a user of the system to respond to alarm signals generated by a customer service center, and the customer service center to respond to alarm signals generated by the user, the interactive system comprising:
 - A. a pharmacy data terminal being adapted to record personal and prescription information of the user;
 - B. a reader for a coding means on a prescription dispenser identifying at least one prescription taken by the user, the coding means being at least one selected from the group consisting of a bar code and a radio frequency identification tag;
 - C. the customer service center communicating with the pharmacy data terminal, the reader, and the user in order to create a permanent patient data base;
 - D. the customer service center providing electronic data storage and prescription information for the user and communicating with a data processing center, in order to provide prescription information;
 - E. the customer service center being connected to a prescription compliance alarm;
 - F. the prescription compliance alarm being connected to a dispenser for medication;
 - G. the reader including an activation means for

10

5

10

15

5

the prescription compliance alarm adapted to signal use or non use of the dispenser and to cause a response to non use;

- H. the activation means including at least one selected from the group consisting of a console receiving and displaying a prescription compliance messages and an audio alarm;
- I. the reader being adapted to read the coding means and being connected to the activation means; and
- J. the reader serving to deactivate the alarm when a proper medication code is provided.
- 16. The interactive prescription compliance and personal safety system of Claim 15 further comprising:
 - A. the reader providing a display means, the display means being selected from the group consisting of liquid crystal display and a television screen;
 - B. the reader including an activating means for sounding an audio alarm;
 - C. the audio alarm providing an indication of when to take medication;
 - D. the audio alarm cooperating with the reader in order to provide an indication of whether medication is proper; and
 - E. the reader informing the data processing center of compliance or non compliance.
- 17. The interactive prescription compliance and personal safety system of Claim 16 further comprising:
 - A. the reader receiving information of medication by the user from the coding means;
 - B. the reader generating a signal; and
 - C. the reader sending the signal to the data processing center in order to verify medication being taken.

5

10

15

5

10

15

18. The interactive prescription compliance and personal safety system of Claim 17 further comprising:

- A. the reader receiving information of at least one service provider;
- B. the data processing center using conventional communications links, accepting all required data for the user, and, creating a permanent patient data base;
- C. the data processing center having prescription information of least one selected from the group consisting of dosage, time interval, and level of service options and accessories is stored;
- D. the data processing center generating a prescription compliance alarm in order for the user to cause medication to be dispensed; and
- E. the data processing center generating a noncompliance alarm after a personal safety alarm is detected.
- 19. A method of providing interactive prescription compliance and life safety alarms for a user, the method comprising:
 - A. providing a patient prescription record for at least one medication and life safety profile in a database;
 - B. generating prescription compliance alarm from the profile and the database;
 - C. downloading the database through the compliance alarm to require the user to remove medication from a dispenser;
 - D. causing the user to pass the medication in front of reader;
 - E. generating a compliance signal to the data base in order to verify medication removal from the dispenser in order to indicate compliance; and
 - F. recording the compliance in the database.


33

- 20. The method of Claim 19 further comprising:
- A. generating a life safety alarm signal;


5

10

- B. transmitting the life safety alarm signal to the database thereby recording date, time, and nature of the safety alarm signal;
- C. relaying the life safety alarm to a correct authority;
 - D. monitoring a service provider, an equipment provider and medical life support equipment;
 - E. providing an interactive audio and video system in a home of the user;
 - F. controlling the interactive audio and video system in a home of the user through a designated third party; and
 - G. utilizing a home telephone number and assigning that number to a pager-like device in order to provide compliance alarms, which is stored and activated at appropriate medication times.









F19.2

F19.4.


PCT/US99/15612



F19.5



F19.6



F19.7

INTERNATIONAL SEARCH REPORT

International application No. PCT/US99/15612

A. CLASSIFICATION OF SUBJECT MATTER IPC(6) :G08B 21/00					
US CL :340/573.1, 825.36; 364/400; 379/38 According to International Patent Classification (IPC) or to both national classification and IPC					
	DS SEARCHED				
Minimum d	ocumentation searched (classification system follower	d by classification symbols)	·		
U.S. :	340/573.1, 825.36; 364/400; 379/38				
Documental NONE	tion searched other than minimum documentation to the	extent that such documents are included	in the fields searched		
Electronic data base consulted during the international search (name of data base and, where practicable, search terms used) NONE					
c. Doc	UMENTS CONSIDERED TO BE RELEVANT				
Category*	Citation of document, with indication, where ap	propriate, of the relevant passages	Relevant to claim No.		
A	US 5,512,935 A (MAJETI ET AL.) 3 the Abstract and figure 1.	0 April 1996 (30/04/96), see	1-20		
A	US 5,623,242 A (DAWSON, JR. (22/04/97), see entire document, espec		1-20		
A, P	US 5,852,408 A (CHRISTIANSEN ET AL.) 22 December 1998 1-20 (22/12/98), see the Abstract.				
		_			
	S. C.	C			
Further documents are listed in the continuation of Box C. See patent family annex.					
·A· do	secial categories of cited documents: becument defining the general state of the art which is not considered be of particular relevance	"T" later document published after the int date and not in conflict with the app the principle or theory underlying the	lication but cited to understand		
•B• •a	rlier document published on or after the international filing date	"X" document of particular relevance; the considered novel or cannot be conside when the document is taken alone	se claimed invention cannot be ared to involve an inventive step		
cit sp	seument which may throw doubts on priority claim(s) or which is ted to establish the publication date of another citation or other secial reason (as specified)	"Y" document of particular relevance; the considered to involve an inventive	step when the document is		
m.	neument referring to an oral disclosure, use, exhibition or other sense occument published prior to the international filing date but later than	combined with one or more other suc being obvious to a person skilled in	the art		
the priority date claimed					
Date of the actual completion of the international search Date of mailing of the international search report 21 OCT 1999					
Name and mailing address of the ISA/US Authorized officer					
Commissioner of Patents and Trademarks Box PCT Washington, D.C. 20231 GLEN R. SWANN, III					
Facsimile N	No. (703) 305-3230	Telephone No. (703) 305-4384			